

S26 36IN/16GA/ULSF2



Product features and benefits

- Ceramic housings designed specifically for high temperature halogen and metal halide applications
- High quality contact materials for optimal mechanical and electrical properties
- UL recognized and CE certified

Areas of application

- Halogen Fixtures
- Metal Halide Fixtures
- Halogen Instrumentation
- Halogen Equipment

Product datasheet

Technical data

General product information

Product Number	69012
Product Name	S2636IN16GAULSF2 100/CS 20/SKU
Ordering Abbreviation	S26 36IN/16GA/ULSF2
Brand Name	OSRAM
General Description	S26 Socket AWG16 SF2 36" Leads (URC)
CSA File No.	LR20904
Old Part Number	F599580

Electrical data

Maximum Wattage (W)	3000 W
Maximum Voltage (V)	600 V

Physical attributes

Length (in)	1.562 in
Length (mm)	39.7 mm
Width (in)	0.968 in
Width (mm)	24.6 mm
Height (in)	1.49 in
Height (mm)	37.8 mm
Body Material	Ceramic Steatite/Aluminum/Plated Steel
Contact Material	Silver Plated Brass
Wire Type	SF2
Wire Gauge (AWG)	16 AWG
Wire Color(s)	White
Lead Length (in)	36 in
Lead Length (mm)	915 mm
Lead Strip Length (in)	0.25 in
Lead Strip Length (mm)	6 mm

Additional product data

Lamp Base Reference	R7s, RX7s Recessed Single Contact (RSC)
Maximum Operating Temperature (°C)	200 C
Rohs Compliant	Yes
Underwriters Laboratories File No.	E31557

Product datasheet



S26 100 DPI Double-Ended Lampholders

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69012	4052899230262	Shipping box (Case)	20	10.1 in x 7.4 in x 2.4 in	2.4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.