



## Power Strip XO CPVT6RD-M

1x powerCON TRUE1 IN – 6x powerCON® TRUE1® TOP  
OUT - Power Meter



Power Strip Xtreme Outdoor (XO) is a compact distribution solution for mobile outdoor applications where power meter is required. Rugged EASYLEN® housing is ideally suited for outdoor usage and demanding applications under harsh conditions. 1x powerCON® TRUE1® TOP In, 6x powerCON® TRUE1® TOP Out, Power Meter.



## Features & Benefits

- Extreme robust and safe EASYLEN® housing with leather grain texture
- Highly reliable NEUTRIK® powerCON® TRUE1® TOP recepticals for In, Out and Daisy chaining
- Flame retardant (UL94-V2) and non-conductive housing material
- High outdoor protection (IP65, IK,..)
- Meter with protected and lit voltage and current consumption display
- Light weight, compact and stackable housing design
- Versatile mounting options

## Market & Applications

- Markets: Professional video wall / lighting / audio
- Mobile application: Festivals, live events
- Semi-permanent applications: Theaters, studios

## Article Variations

Article name	Details	Order code
CPVT6RD-M	IN: 1 x powerCON® TRUE1® TOP - OUT: 6 x powerCON® TRUE1® TOP – Power Meter	1035587

## Technical Information

Product	
<b>Input device</b>	1x powerCON®TRUE1®TOP with self-closing caps
<b>Output device</b>	6x powerCON®TRUE1®TOP with self-closing caps
<b>Daisy chaining</b>	1x powerCON®TRUE1®TOP with self-closing caps
<b>Power meter</b>	Protected and lit screen with current and voltage display

Electrical	
<b>Contact resistance / protection class</b>	Protection class II
<b>Dielectric strength</b>	0,5 kV / mm
<b>Rated voltage</b>	250V AC
<b>Rated Current</b>	16A (USA: 20A)
<b>Number of electrical contacts</b>	2 + PE
<b>Phases</b>	single-phase

Mechanical	
<b>Lifetime</b>	> 5000 Mating cycles per connector
<b>Dimensions</b>	380 x 91.2 x 77 mm
<b>Conductor cross section</b>	2.08 mm <sup>2</sup>
<b>Weight</b>	1.27 kg
<b>Mounting options</b>	Truss clip, mounting wholes for pegging or suspension

## Material

<b>Housing</b>	Easylen
<b>Color</b>	black

## Environmental

<b>Standards compatibility</b>	UL94-V2
<b>Protection class</b>	IP65
<b>Temperature range</b>	-25 °C bis +50°C