

# RT4MPR

4 pole male TINY xlr receptacle, rear mountable



## Article Variations

Article Name	Details	Packaging
RT4MPR	Nickel plated housing, gold plated contacts, max. panel thickness: 3 mm	Plastic Bag
RT4MPR-D	Nickel plated housing, gold plated contacts, max. panel thickness: 3 mm	BULK

## Technical Information

Product	
Title	RT4MPR
Connection Type	XLR

Electrical	
Contact Resistance	$\leq 10 \text{ m}\Omega$
Insulation Resistance	$> 1 \text{ G}\Omega$
Dielectric Strength	$> 500 \text{ V rms}$
Rated current per contact	$< 5 \text{ A}$

Mechanical	
Lifetime	$> 1000 \text{ Mating Cycles}$
Wiresize	$0.22 \text{ mm}^2$
Wiresize	24 AWG

<b>Material</b>	
<b>Housing</b>	Zinc
<b>Nut</b>	Brass
<b>Washer</b>	Steel
<b>Plastic Body</b>	PA66+30%GF
<b>Pin</b>	Brass
<b>Housing</b>	Nickel Plating
<b>Nut</b>	Nickel Plating
<b>Washer</b>	Nickel Plating
<b>Pin</b>	Gold Plating