







GENERAL INFO

Brand Model Name Code Number EAN Number

LIGHT SOURCE

Source CCT Luminous Flux Lux Source Life Expectancy Optical aperture degrees

OPTICS

Zoom Lens Diameter Lens Type Focus

COLOUR SYSTEM

Colour Mixing CCT

Colour Wheel

Animation Wheel Rotation Gobos

Gobo Size

Circular Prism Frost 450W White LED module 6500K 21000Lm 26000lux@10M More than 20000H 16mm

Triton Blue

10297862

Halley H450

7427254442852

4° to 53° 133mm Optical glass Motorized focus

CMY infinite color mixing CTO color temperature linear adjustment(3000K-6500K) 5 basic color filter+CRI+white

DYNAMIC EFFECTS

One WATER effects wheel 7 glass patterns + white circle, pluggable and replaceable Outer diameter is 22.9mm Inner diameter is 15mm 4-Facet prism 1°light frost

NOISE LEVEL

SLN Fan Mode Auto Fan Mode Theatre Fan Mode Constant Fan Mode

CONTROL

Protocols DMX Channels RDM Display Firmware Upgrade

ELECTRONICS

Dimmer

Dimmer Curves

Strobe / Shutter

Display Battery Operating Temperature Led Control

ELECTRICAL

Mains Power Supply Max Power Consumption Output (at 230v) Power Factor Inrush Current 30DB 42DB 38DB 46DB

DMX512, RDM, ArtNet 33CH, 36CH 5pin XLR input and output LCD liquid crystal screen Software upgrade via USB or DMX interface

Electronic dimming, 0-100% linear dimming, uniform light spot Linear dimming SQUARE 1/SQUARE 2/S-CURVE Electronic strobe, 1-25 times/second NI-MH battery 0°C~40°C LED refresh rate: 1000Hz~25KHz

AC 100-240V ~ 50/60Hz 520W 520W 0.98 5.2A/110V; 2.6A/220V

PHYSICAL

IP Rating Cooling Suspension and Fixing Pan / Tilt Lock Signal Connection

Data Connection

Power Connection Weight Dimensions Master Carton QTY Master Carton Working temperature range

BODY

Hardware on-board

Pan Tilt Pan/Tilt Resolution

Body

Body Colour

IP20 By fan Foldable light hook Only Tilt lock Locking 5 pin XLR IN/ OUT NEUTRIK Five-core signal input/ output NEUTRIK NEUTRIK RJ45 26.3kg 495*365*755mm

1 in 1 0°C~40°C

540°

270°

housing

Black

Aluminum and steel structure with plastic covers

X axis: 540° 8bit /16 bit

Engineering plastic PA66

precision scanning Y axis: 270° 8bit /16 bit precision scanning

ACCESSORIES

Accessories Included

Accessories Optional

User manual, Warranty card, Certificate of conformity, Bracket, PowerCOM, DMX cable, Safety cord

Halley H450 Flightcase

CERTIFICATIONS / APPROVALS

Certifications

CE, RoHs

ACCESSORIES HALLEY H450 FLIGHTCASE







1st - VERSION 01/2025