



COMPACT500

500W amplified sound system with a subwoofer and 2 satellites - Supplied with speaker stands and mounts + cables

Code : 10302

EAN : 3662009013732

Technical data

SATELLITE

- Power output : 80W RMS - 160W max
- Frequency response : 155Hz -22KHz
- Sensitivity(1W@1m) : 93 dB
- SPL max. (@1m) : 120 dB
- Nominal impedance : 8 Ohms
- Boomer : 4,75"
- HF driver : 1" compression
- Dispersion : 90° x 45° (HxV)
- Connector : 1 x Jack
- Fixation system : 1 M6 rigging point and 18mm mounting plate
- Dimensions : 225 x 140 x 110 mm
- Net weight : 1.9 kg

SUBWOOFER

- Power output : 350W RMS - 700W max
- Frequency response : 50 - 160Hz
- Sensitivity(1W@1m) : 90 dB
- SPL max. (@1m) : 120 dB
- Nominal impedance : 8 Ohms
- Boomer : 10"
- Fixation system : 1x25mm mounting plate (on top)
- Dimensions : 345 x 450 x 400 mm
- Net weight : 14.5 kg

AMPLIFIER

- LF : 1 x 350W RMS / Classe D - 4 Ohms
- HF : 2 x 80W RMS / classe D - 8 Ohms
- Inputs :
 - 3 x Combo XLR/Jack inputs
 - Line/Micro
 - 1 x RCA / 1 x Jack 3.5 stereo line input
- Outputs :
 - 2 x Jack line output
 - 1 x Jack link output
 - 2 x jack satellites output
- DSP : Vocal-Flat-Music for each input
- Output level : Volume settings for each output
- Subwoofer : Main volume settings
- Balance : Left/Right output volume control
- Switches :
 - 1 x CH2 thru/REOut
 - 1 x Satellites mono or stereo setup